

BONDS ON[®]

READY-MIXED, POURABLE LATEX CONCRETE CRACKFILLER

WALL FIRMA, INC.

Waterproofing and Repair Products Since 1949.
733 E. Main Street
Monongahela, PA 15063-1499

1-800-333-4333
1-724-258-6873
Fax: 724-258-3188
e-mail: wfi@wallfirma.com
website: www.wallfirma.com

FOR HORIZONTAL SURFACES

DESCRIPTION:

Repairs cracks up to 1/2" wide and 1" deep. Excellent for all horizontal concrete surfaces including driveways and floors. The gray color will blend with most concrete surfaces. Under normal conditions, area will be ready for traffic in 30 minutes.

USES:

Excellent for:

Indoor Floors:

- * Basements
- * Garages

EXTERIOR AREAS:

- * Concrete Driveways
- * Expansion Joints
- * Concrete Walks
- * Patios/Pool Areas

ADVANTAGES:

- * Use indoors and Outdoors
- * Ready for traffic in 30 minutes
- * Pliable, high-strength formula

SURFACE PREPARATIONS:

Remove all loose debris, vegetation, grease, oil, and dirt from the crack. Dry the surface before applying product.

APPLICATION:

Fill the crack in 1/4" layers, allowing a minimum of 24 hours drying time between applications. When applying to deep cracks more than 1/8" wide, first fill the crack with silica sand to within 1/4" of the surface. It is recommended to slightly overfill the crack, since product shrinks when cured.

LIMITATIONS:

- Use only on horizontal surface.
- Do not apply when rain is expected within 24 hours or when temperatures are below 40° F.
- Store in areas where temperatures are above freezing.
- Do not use on cracks wider than 1/2 inch.

CLEAN UP:

Wash hands, clothing and tools immediately with warm, soapy water. Clean up spills immediately with warm water.