

DRY AWAY®

READY-MIX, LATEX-BASE MASONRY WATERPROOFING PAINT

WALL FIRMA, INC.

Waterproofing and Repair Products Since 1949.
733 E. Main Street
Monongahela, PA 15063-1499

1-800-333-4333
1-724-258-6873
Fax: 724-258-3188
e-mail: wfi@wallfirma.com
website: www.wallfirma.com

FOR INTERIOR/EXTERIOR WALLS

DESCRIPTION:

A heavy bodied acrylic-latex coating for exterior and interior applications that will provide a waterproof barrier while filling and sealing porous masonry surfaces. The coating is fast drying and provides for easy clean-up with warm water and soap. Excellent to use on exterior or interior walls of basements and garages, above or below grade.

USES:

- Concrete Blocks
- Cinder Blocks
- Poured Concrete
- Stucco
- Foundations
- Brick

ADVANTAGES:

- Interior/Exterior
- Above/Below Grade
- Eliminates Dampness
- Very Slight Odor
- Easy Clean-up
- Environmentally Safe

SURFACE PREPARATION:

Masonry surfaces must be clean and free from grease, dirt, frost or loose paint. If powdery, salt-like deposits (called efflorescence) are present on the surface, remove then with a muriatic acid or concrete etcher, in accordance with manufacturer's directions. Repair all cracks and holes, including active water leaks, with Firma Plug® Hydraulic Cement.

APPLICATION:

Mix thoroughly before using.

DO NOT THIN or MIX with other paints or coatings.

Dry Away Latex Waterproof Paint must be applied full-bodied. Apply a generous coat, using a short bristled brush or long-nap roller.

Work coating into all pores and voids, completely covering the surface. Allow the first coat to dry 24 hours before applying the second coat.

TWO COATS ARE RECOMMENDED FOR BEST RESULTS.

Do not apply when surface temperature is below 50 degrees Fahrenheit. Do not overspread; waterproofing performance will be affected

NOTE: For best results, apply to bare, unsealed surface. This product may be applied to previously painted surfaces, but effectiveness will only be as good as existing coating to which it is applied.

COVERAGE:

On rough, porous surfaces, covers up to 100 sq. ft. per gallon; smooth concrete or previously painted surfaces, up to 150 sq. ft. per gallon.

TINTING:

May be tinted to light shades with universal tinting colors. Approximate pastel colors may be obtained by using the quart formulation per gallon coating. Colors may not match exactly to color chart, but will be close.

DRYING TIME:

Most surfaces will be dry to touch in 1 - 2 hours. Allow surface to dry at least 24 hours or until completely dry before applying the second coat.

CLEAN-UP:

Clean hands and tools immediately after use with warm water and soap.

LIMITATIONS:

- Do not apply at temperatures below 50° F or when it is expected to be below 50° F within 8 hours of application.
- Do not thin this product.

TECHNICAL SUPPORT DATA:

See Technical Data Sheet.

WALL FIRMA, INC.
January 2006

WALL FIRMA, INC.