

FIRMAGLAZE™ SPECIAL

SOLVENT-BASED, HIGH-GLOSS CLEAR ACRYLIC SEALER

WALL FIRMA, INC.

Waterproofing and Repair Products Since 1949.
733 E. Main Street
Monongahela, PA 15063-1499

1-800-333-4333
1-724-258-6873
Fax: 724-258-3188
e-mail: wfi@wallfirma.com
website: www.wallfirma.com

FOR CONCRETE & MASONRY

DESCRIPTION:

Firmaglaze Special is a clear, non-yellowing acrylic sealer for concrete and masonry surfaces. This formulation is an all acrylic based methyl methacrylate

copolymer, that will provide a tough, durable, yet flexible sealer for concrete and masonry surfaces. This surface has excellent resistance to chemical fumes, lime, and alkali.

USES:

EXTERIOR AGGREGATE, MARBLE-CRETE AND CEMENTITIOUS COMPOSITE PANELS

Provides maximum protection, protects coloration from fading, eliminates freeze-thaw cycle damage and provides a clear, durable, glossy finish.

STONE

Protects against discoloration, weatherization of surface, efflorescence and laitance. Seals small surface cracks.

CEMENTITIOUS COATINGS

Provides for a tile-like finish, and makes surfaces easy to clean. Excellent for use over Wall Dri Masonry Waterproof Coating and Firmasheen surfaces where a clear, glossy finish is desired. Protects aluminum surfaces against cement and mortar spills during construction.

APPLICATION:

Surface must be completely clean and dry throughout. Remove all dirt, dust, wax, efflorescence, defective paints and coatings. No moisture should remain in the area prior to treating. Thinning is normally not recommended. However, if needed, use only mineral spirits at NOT MORE THAN ONE PINT PER GALLON.

Apply with roller, brush or low pressure spray.

Apply liberally until surface is completely sealed. Two coats are recommended.

Make sure the area is completely dry before applying Firmaglaze Special.

Allow sufficient time for one coat to cure before applying the next coat. Usually about 2 hours; drying time is affected by climatic conditions.

Clean all tools and any spillage immediately with mineral spirits.

LIMITATIONS:

Do not apply to frozen or frost covered surfaces.

Protect all surfaces not to be sealed

Firmaglaze Special is not recommended for use on the following surfaces:

- Composition shingles
- Sidings or floorings
- Asphalt surfaces
- Sealing heavy duty floor
- Floors exposed to underground water
- Slate and quarry tile surfaces
- Ceramic surfaces
- Slate floors and patios
- Concrete slabs